

Technical Specification EPA

Spare parts
Ersatzteile
Pièces détachées
Reserve onderdelen
Repuestos
Reservdelar

TECHNICAL SPECIFICATIONS CHAINSAW

Jonsered

	cu.inch cm³	inch mm	inch mm	kW/hp	rpm	dB(A)	m/s²	model Champion/NGK		us pint lit	us pint lit				ml/min 8500 rpm	inch	inch	lbs kg	kW/lbs kW/kg	TURBO															
2095 TURBO	5.7 93.5	2.2 56	1.5 38	4.9/6.7	2500	101/111	5.3/10.3	EM/ET	RCJ 7Y/ BPMR 7A Tillotson HS 297A	1.84 0.87	1.37 0.65	-	•	•	12.8-31.2	18-32	3/8	18.0 8.2	0.27 0.60	•	3-pro	•	-	•	-	-	-	-	-	-	-	-	-		
2083 II TURBO	4.7 76.5	2.0 52	1.4 36	4.0/5.4	2700	102/112	2.1/5.5	EM/ET	RCJ 7Y/ BPMR 7A Walbro WJ 77	1.80 0.85	0.85 0.40	-	•	•	4.0-20.0	18-28	3/8	14.9 6.8	0.27 0.59	•	3-pro	-	•	•	-	-	-	-	-	-	-	-	-		
2171 W TURBO	4.3 70.7	2.0 50	1.4 36	3.9/5.3	2700	102.5/112	4.6/5.2	SEM/CD	RCJ 7Y/ BPMR 7A Walbro HD 12B	1.63 0.77	0.89 0.42	-	•	•	4.0-20.0	15-28	3/8	13.8 6.3	0.28 0.62	•	3-pro	•	•	•	•	%	•								
2171 TURBO	4.3 70.7	2.0 50	1.4 36	3.9/5.3	2700	102.5/112	4.6/5.2	SEM/CD	RCJ 7Y/ BPMR 7A Walbro HD 12B	1.63 0.77	0.89 0.42	-	•	•	4.0-20.0	15-28	3/8	13.4 6.1	0.29 0.64	•	3-pro	•	•	•	•	-	-	-	-	-	-	-	-		
2165 TURBO	4.0 65.1	1.9 48	1.4 36	3.4/4.6	2700	102/113	3.6/5.7	SEM/CD	RCJ 7Y/ BPMR 7A Walbro HD 12B	1.63 0.77	0.89 0.42	-	•	•	4.0-20.0	15-28	3/8	13.2 6.0	0.26 0.57	•	3-pro	•	•	•	•	-	-	-	-	-	-	-	-	-	
2163 W TURBO	3.8 62.4	1.9 47	1.4 36	3.4/4.6	2700	102/112	3.3/3.1	SEM/CD	RCJ 7Y/ BPMR 7A Walbro HD 12B	1.63 0.77	0.89 0.42	-	•	•	4.0-20.0	13-24	.325 3/8	13.6 6.2	0.25 0.55	•	3-pro	•	•	•	•	%	-								
2163 TURBO	3.8 62.4	1.9 47	1.4 36	3.4/4.6	2700	102/112	3.3/3.1	SEM/CD	RCJ 7Y/ BPMR 7A Walbro HD 12B	1.63 0.77	0.89 0.42	-	•	•	4.0-20.0	13-24	.325 3/8	13.2 6.0	0.26 0.57	•	3-pro	•	•	•	•	%	-								
2159 W TURBO	3.6 59.0	1.9 47	1.3 34	3.0/4.1	2700	102/112	3.9/4.4	SEM/CD	RCJ 7Y/ BPMR 7A Walbro HDA 191	1.44 0.68	0.80 0.38	-	•	•	5.0-15.0	13-20	.325 3/8	12.5 5.7	0.24 0.53	•	3-pro	•	-	•	•	%	•								
2159 TURBO	3.6 59.0	1.9 47	1.3 34	3.0/4.1	2700	102/112	3.9/4.4	SEM/CD	RCJ 7Y/ BPMR 7A Walbro HDA 175	1.44 0.68	0.80 0.38	-	•	•	5.0-15.0	13-20	.325 3/8	12.4 5.6	0.24 0.54	•	3-pro	•	-	•	•	-	-	-	-	-	-	-	-	-	
2054 W TURBO	3.0 49.0	1.73 44	1.3 32	2.6/3.5	2600	100/108	3.3/8.6	FHP/ET	RCJ 7Y/ BPMR 7A Walbro HDA 143A	1.18 0.56	0.80 0.38	-	•	•	4.2-8.5	13-18	.325 3/8	11.5 5.2	0.20 0.44	•	3-pro	•	•	•	•	%/-	-								
2054 TURBO	3.0 49.0	1.73 44	1.3 32	2.6/3.5	2600	100/108	3.3/8.6	FHP/ET	RCJ 7Y/ BPMR 7A Walbro HDA 143A	1.18 0.56	0.80 0.38	-	•	•	4.2-8.5	13-18	.325 3/8	11.5 5.2	0.20 0.44	•	3-pro	•	•	•	•	-	-	-	-	-	-	-	-	-	
2149 W TURBO CAT	3.0 49.4	1.7 44	1.3 32.5	2.3/3.1	2700	101/112	3.7/2.9	SEM/CD	RCJ 7Y/ BPMR 7A Walbro HDA 159A	1.06 0.50	0.59 0.28	-	-	•	5.0-10.0	13-20	.325	11.0 5.0	0.20 0.45	•	3-pro	•	-	•	•	%/-	•								
2149 TURBO CAT	3.0 49.4	1.7 44	1.3 32.5	2.3/3.1	2700	101/112	3.7/2.9	SEM/CD	RCJ 7Y/ BPMR 7A Walbro HDA 159A	1.06 0.50	0.59 0.28	•	•	•	5.0-10.0	13-20	.325	10.8 4.9	0.21 0.46	•	3-pro	•	-	•	•	-	-	-	-	-	-	-	-	-	
2149W TURBO	3.0 49.4	1.7 44	1.3 32.5	2.3/3.1	2700	101/112	3.7/2.9	SEM/CD	RCJ 7Y/ BPMR 7A Walbro HDA 159A	1.06 0.50	0.59 0.28	•	•	•	5.0-10.0	13-20	.325	11.0 5.0	0.21 0.47	•	3-pro	•	-	•	•	%	•								
2149 TURBO	3.0 49.4	1.7 44	1.3 32.5	2.3/3.1	2700	101/112	3.7/2.9	SEM/CD	RCJ 7Y/ BPMR 7A Walbro HDA 159A	1.06 0.50	0.59 0.28	-	•	•	5.0-10.0	13-20	.325	10.8 4.9	0.21 0.47	•	3-pro	•	-	•	•	-	-	-	-	-	-	-	-	-	-
2150 TURBO	3.0 49.4	1.7 44	1.3 32.5	2.3/3.1	2700	102/109.5	3.2/4.0	SEM/CD	RCJ 7Y/ BPMR 7A Walbro HDA 159A	1.06 0.50	0.53 0.25	-	•	•	5.0-10.0	13-18	.325	10.8 4.9	0.21 0.47	•	3-pro	•	-	•	•	-	-	-	-	-	-	-	-	-	-
2145 TURBO	2.7 45.0	1.7 42	1.3 32.5	2.2/3.0	2700	101/110	3.2/4.0	SEM/CD	RCJ 7Y/ BPMR 7A Walbro HDA 159A	1.06 0.50	0.53 0.25	-	•	-	9.0	13-18	.325	10.8 4.9	0.20 0.45	•	3-pro	•	-	•	•	-	-	-	-	-	-	-	-	-	-
2040 TURBO	2.5 40.2	1.6 40	1.3 32	1.9/2.6	3000	98/104	5.1/5.9	Phelon/CD	RCJ 7Y/ BPMR 7A Walbro WT 289	0.87 0.41	0.42 0.20	-	-	-	6.0-8.0	13-15	.325	10.1 4.6	0.19 0.41	•	3-pro	-	-	•	•	-	-	-	-	-	-	-	-	-	-
2036 TURBO	2.2 36.3	1.5 38	1.3 32	1.6/2.2	3000	98/104	4.2/5.8	Phelon/CD	RCJ 7Y/ BPMR 7A Walbro WT 289	0.87 0.41	0.42 0.20	-	-	-	6.0-8.0	14-16	3/8	10.1 4.6	0.16 0.35	•	3-pro	-	-	•	•	-	-	-	-	-	-	-	-	-	-
2116 EL	-	-	-	1.6/2.2	-	81/101	4.5/7.0	-	-	-	0.21 0.10	-	-	-	5.0 (7500)	14-16	3/8	8.2 3.7	0.19 0.43	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	

* Guide bar length may vary according to the market where sold. ** Heated carburettor only available in certain markets. Valid for EPA approved versions only.

108 88 53-10

jonsered.com