

Technical Specification CE

Spare parts
Ersatzteile
Pièces détachées
Reserve onderdelen
Repuestos
Reservdelar

TECHNICAL SPECIFICATIONS CHAINSAW **Jonsered**

	cm ³	mm	mm	kW/hp	rpm	rpm	dB(A)	m/s ²		model Champion/NGK		lit	lit			ml/min 8500 rpm	inch	inch	kg	kW/kg	TURBO							
2095 TURBO	93,6	56	38	4,9/6,7	2400	13000	101/111	5,3/10,3	EM/ET	RCJ 7Y/ BPMR 7A	Tillotson HS 265A	0,87	0,65	-	•	•	12,8-31,2	18-32	3/8	8,2	0,60	•	3-pro	•	-	•	-	
2077 TURBO	76,5	52	36	4,0/5,4	2700	13500	101,5/109,5	2,3/5,2	EM/ET	RCJ 7Y/ BPMR 7A	Walbro WJ 28C	0,85	0,40	-	•	•	5,7-28,3	18-28	3/8	6,8	0,59	•	3-pro	-	•	•	-	
2171/2171 W TURBO	70,7	50	36	3,9/5,3	2700	13500	102/111	4,6/5,2	SEM/CD	RCJ 7Y/ BPMR 7A	Walbro HD 6B	0,77	0,42	-	•	•	4,0-20,0	15-28	3/8	6,1/6,3	0,64/0,62	•	3-pro	•	•	•	% (W)	•
2165 TURBO	65,1	48	36	3,4/4,6	2700	12500	102/111	3,6/5,7	SEM/CD	RCJ 7Y/ BPMR 7A	Zama EL 2C	0,77	0,42	-	•	•	4,0-20,0	15-28	3/8	6,0	0,57	•	3-pro	•	•	•	-	•
2163/2163 W TURBO	62,4	47	36	3,4/4,6	2700	13500	102/110	3,3/3,1	SEM/CD	RCJ 7Y/ BPMR 7A	Walbro HD 6B	0,77	0,42	-	•	•	4,0-20,0	13-24	.325 3/8	6,0/6,2	0,57/0,55	•	3-pro	•	•	•	% (W)	-
2159/2159 W TURBO	59,0	47	34	3,0/4,1	2700	13500	102/110,6	3,9/4,4	SEM/CD	RCJ 7Y/ BPMR 7A	Walbro HDA 174	0,68	0,38	-	•	•	5,0-15,0	13-20	.325 3/8	5,6/5,7	0,54/0,53	•	3-pro	•	-	•	% (W)	•
2055/2055 W TURBO	53,2	46	32	2,8/3,8	2500	14800	102/109	3,3/6,2	FHP/ET	RCJ 7Y/ BPMR 7A	Walbro HDA 119A	0,56	0,38	-	-	•	4,2-8,5	13-18	.325 3/8	5,2	0,54	•	3-pro	-	•	•	% (W)	-
2055 W TURBO CAT	53,2	46	32	2,7/3,7	2500	14800	102/110	3,3/6,2	FHP/ET	RCJ 7Y/ BPMR 7A	Walbro HDA 119A	0,56	0,38	•	-	•	4,2-8,5	13-18	.325 3/8	5,5	0,49	•	3-pro	-	•	•	% (W)	-
2054/2054 W TURBO	53,2	46	32	2,6/3,5	2500	13000	100/108	3,3/8,6	FHP/ET	RCJ 7Y/ BPMR 7A	Walbro HDA 119A	0,56	0,38	-	-	•	4,2-8,5	13-18	.325 3/8	5,2	0,50	•	3-pro	•	•	•	% (W)	-
2149/2149 W TURBO	49,4	44	32,5	2,3/3,1	2700	13000	101/108	3,7/2,9	SEM/CD	RCJ 7Y/ BPMR 7A	Walbro HDA 154C	0,50	0,28	-	•	•	5,0-10,0	13-20	.325	4,9/5,0	0,47/0,46	•	3-pro	•	-	•	% (W)	•
2149/2149 W TURBO CAT	49,4	44	32,5	2,3/3,1	2700	13000	101/108	3,7/2,9	SEM/CD	RCJ 7Y/ BPMR 7A	Walbro HDA 154C	0,50	0,28	•	•	•	5,0-10,0	13-20	.325	4,9/5,0	0,47/0,46	•	3-pro	•	-	•	% (W)	•
2150 TURBO	49,4	44	32,5	2,3/3,1	2700	13000	102/109,5	3,2/4,0	SEM/CD	RCJ 7Y/ BPMR 7A	Walbro HDA 154C	0,50	0,25	-	•	•	5,0-10,0	13-18	.325	4,9	0,47	•	3-pro	•	-	•	-	•
2145 TURBO	45,0	42	32,5	2,2/3,0	2700	12500	101/110	3,2/4,0	SEM/CD	RCJ 7Y/ BPMR 7A	Walbro HDA 154C	0,50	0,25	-	•	-	9,0	13-18	.325	4,9	0,45	•	3-pro	•	-	•	-	•
2141 TURBO	40,8	40	32,5	2,0/2,7	2700	12500	101/110	3,2/4,0	SEM/CD	RCJ 7Y/ BPMR 7A	Walbro HDA 154C	0,50	0,25	-	•	-	9,0	13-18	.325	4,9	0,41	•	3-pro	-	-	•	-	-
2040 TURBO	40,2	40	32	1,9/2,6	3000	13000	98/104	5,1/5,9	Phelon/CD	RCJ 7Y/ BPMR 7A	Walbro WT 239	0,41	0,20	-	-	-	8,0	13-15	.325	4,6	0,41	•	3-pro	-	-	•	-	-
2036 TURBO	36,3	38	32	1,6/2,2	3000	13000	98/104	4,2/5,8	Phelon/CD	RCJ 7Y/ BPMR 7A	Walbro WT 239	0,41	0,20	-	-	-	8,0	14-16	3/8	4,6	0,35	•	3-pro	-	-	•	-	-
2035 TURBO	36,3	38	32	1,4/1,9	3000	13000	91/101	4,2/6,8	Phelon/CD	RCJ 7Y/ BPMR 7A	Walbro WT 391	0,38	0,20	-	-	-	8,0	14-16	3/8	4,7	0,30	•	5	-	-	•	-	-
2033 TOP-HANDLE	33,0	37	30	1,2/1,6	2900	11000	96/102	4,5/7,0	Phelon/CD	RCJ 8/-	Walbro WT 404	0,23	0,15	-	-	•	6,0	12-14	3/8	3,1	0,39	-	5	-	-	-	-	-
2118 EL	-	-	-	1,8/2,4	-	-	81/101	4,5/7,0	-	-	-	-	0,10	-	-	5,0 (7500)	14-16	3/8	3,8	0,47	-	-	-	-	-	-	-	-
2115 EL	-	-	-	1,5/2,0	-	-	81/101	4,5/7,0	-	-	-	-	0,10	-	-	4,0 (7700)	14-16	3/8	3,8	0,39	-	-	-	-	-	-	-	-

* Guide bar length may vary according to the market where sold. ** Heated carburettor only available in certain markets. Valid for CE approved versions only.

108 88 54-10

jonsered.com