
































# Technical Specification CE

<b>Spare parts</b>	Replaces	
<b>Ersatzteile</b>	Ersetzt	
<b>Pièces détachées</b>	Remplace	
<b>Reserve onderdelen</b>	Vervangt	
<b>Repuestos</b>	Reemplaza	
<b>Reservdelar</b>	Ersätter	106 28 82-61

# TECHNICAL SPECIFICATIONS CHAINSAW

																																			
	cm <sup>3</sup>	mm	mm	kW/hp	rpm	rpm	dB(A)	m/s <sup>2</sup>		model Champion/NGK		lit	lit			ml/min 9000 rpm		inch	inch	kg	kW/kg	TURBO													
<b>CS 2186/WH</b>	84,7	54	37	4,5/6,1	2500	13000	102/116	6,5/8,1	SEM/CD	RCJ 7Y/ BPMR 7A	Tillotson HS 299A	0,90	0,50	-	•	4-20	↔	18-28	3/8	7,3	0,62	•	3-pro	-	*/-	-/•	•								
<b>CS 2171/WH</b>	70,7	50	36	3,9/5,3	2700	13500	102/112	4,6/5,2	SEM/CD	RCJ 7Y/ BPMR 7A	Walbro HD 6B	0,77	0,42	-	•	4-20	↔	15-28	3/8	6,1/6,3	0,62	•	3-pro	•	*/-	-/•	•								
<b>CS 2165</b>	65,1	48	36	3,4/4,6	2700	12500	102/113	3,6/5,7	SEM/CD	RCJ 7Y/ BPMR 7A	Zama EL 2B	0,77	0,42	-	•	4-20	↔	15-28	3/8	6,0	0,57	•	3-pro	•	*/-	-	•								
<b>CS 2163/WH</b>	62,4	47	36	3,4/4,6	2700	13500	102/112	3,3/3,1	SEM/CD	RCJ 7Y/ BPMR 7A	Walbro HD 6B	0,77	0,42	-	•	4-20	↔	13-24	.325 3/8	6,0/6,2	0,55	•	3-pro	•	*/-	-/•	•								
<b>CS 2159/WH</b>	59,0	47	34	3,0/4,1	2700	13500	102/114	3,9/4,4	SEM/CD	RCJ 7Y/ BPMR 7A	Walbro HDA 198/190	0,68	0,38	-	•	6-17	↔	13-20	.325 3/8	5,6/5,7	0,54/0,53	•	3-pro	•	*/-	-/•	•								
<b>CS 2159 C/WH</b>	59,0	47	34	3,0/4,1	2700	13500	102/114	3,9/4,4	SEM/CD	RCJ 7Y/ BPMR 7A	Walbro HDA 198/190	0,68	0,38	•	•	6-17	↔	13-20	.325	5,6/5,7	0,54/0,53	•	3-pro	•	*/-	-/•	•								
<b>CS 2152 WH</b>	51,7	45	32	2,4/3,3	2700	13000	102/114	3,0/4,1	SEM/CD	RCJ 7Y/ BPMR 7A	Zama C3-EL17	0,50	0,28	-	•	5-12	↔	13-20	.325	5,0/5,1	0,48/0,47	•	3-pro	•	*/-	-/•	•								
<b>CS 2152 C/WH</b>	51,7	45	32	2,4/3,3	2700	13000	102/113	3,0/4,1	SEM/CD	RCJ 7Y/ BPMR 7A	Zama C3-EL17	0,50	0,28	•	•	5-12	↔	13-20	.325	5,0/5,1	0,48/0,47	•	3-pro	•	*/-	-/•	•								
<b>CS 2150</b>	49,4	44	32	2,3/3,1	2700	13000	102/113	3,2/4,0	SEM/CD	RCJ 7Y/ BPMR 7A	Walbro HDA 195	0,50	0,28	-	•	5-12	↔	13-18	.325	4,9	0,47	•	3-pro	•	-/•	-	•								
<b>CS 2145</b>	45,0	42	32	2,2/3,0	2700	12500	101/110	3,2/4,0	SEM/CD	RCJ 7Y/ BPMR 7A	Walbro HDA 195	0,50	0,28	-	•	9	↔	13-18	.325	4,9	0,45	•	3-pro	•	-/•	-	•								
<b>CS 2141</b>	40,8	40	32	2,0/2,7	2700	12500	101/113	3,2/4,0	SEM/CD	RCJ 7Y/ BPMR 7A	Walbro HDA 195	0,50	0,28	-	•	9	↔	13-18	.325	4,9	0,41	•	3-pro	-	-/•	-	-								
<b>CS 2137</b>	42,0	40	32	1,8/2,4	3000	13000	101/111	5,5/8,5	Phelon/CD	RCJ 7Y/ BPMR 7A	Walbro WT 391	0,38	0,29	-	-	4-8	↔	14-16	3/8	4,7	0,38	•	3-pro	•	-/•	-	-								
<b>CS 2118 EL</b>	-	-	-	1,8/2,4	-	-	81/101	4,5/7,0	-	-	-	-	0,10	-	-	5 (7500)	↔	14-16	3/8	3,8	0,47	-	-	-	-	-	-								
<b>CS 2115 EL</b>	-	-	-	1,5/2,0	-	-	81/101	4,5/7,0	-	-	-	-	0,10	-	-	4 (7700)	↔	14-16	3/8	3,8	0,39	-	-	-	-	-	-								

\* Guide bar length may vary according to the market where sold. \*\* Heated carburettor only available in certain markets. Valid for CE approved versions only.  
108 88 83-10

